




Manual, radial-arm, crosscut saw

BEST 1250

For straight (90°) miter (45° left) cross cutting, and bevel cutting at 45° left and right, of wooden-based panels and solid wood boards up to 3mt. For furniture manufacturing and joinery.









VERSATILE

Swivelling arm (0° to 45° left and right) and tilting cutting-head (stop and lock at 45° left) allow many different cutting operations for the greatest versatility.

SAFE

Sound-insulated, full-cover blade guard with safety microswitch, anti-kickback, well-dimensioned working bench, emergency button definitively contribute to the operator safety during the cutting process.

SOLID AND ACCURATE

Rugged steel construction, arm and base made of cast iron.

Interchangeable and tempered-steel made guides. Cutting head sliding on 8 ball bearings for a smooth, precise and effortless carriage mouvement.

Small footprint: well suited to small workshops

Easy to use

Versatile

Useful complement to panel saws



SERVICE

Worldwide after-sale service.

Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs

DATA SHEET

Max. cutting height:	125 mm
Max. cutting width	1155 x 20 h mm
Mincutting width	1060 x 125 h mm
Max.length of workpiece	unlimited
Max. cutting width for ripping	
Height of blade at 45° from the table	0 - 80 mm
Min. and Max. cutting width at 45° (right)	745 - 800 mm
Min. and Max. cutting width at 45° (left)	555 - 610 mm
Height of blade from working bench	0 - 45 mm
Blade diameter	400 mm
Blade bore diameter	30 mm
Motor	HP / KW 4/3 RPM 2800
Working bench dimensions	2400x1580 x 25 mm
Diameter of dust collection nozzle on blade guard	60 mm
Diameter of dust collection nozzle on rear hood	100 mm (n.2)
Overall dimensions of full- assembled machine and net weight	2400x2020x1620 mm / Kg 344
Package dimensions and gross weight	2400 x 1100 x 820 mm 380 Kg
Dimensions and gross weight half assembled machine	Half-assembly for this model is not available



HEAVY-DUTY PROFESSIONAL

Well-dimensioned machine, best suited to cut heavy wooden boards and panels. Max. cutting width up to 1155 mm

CUTTING HEIGHT

CUTTING

90°

WIDTH

MAX JUNIOR 640 BIG 800 BEST 960 **BEST 1250** 90° **45°** ∟ **45°** ∟ **45°** ℝ mm mm mm mm mm mm mm 450 610 430 770 1060 745 456 616 776 464 624 784 1074 474 634 794 95 Ø 400 mm mm 80 486 646 806 1096 65 501 661 821 50 520 680 840 35 705 20

MIN mm MAX

SERVICE

+39 0571 635 433 service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com



MAGGI TECHNOLOGY

Via delle Regioni, 299 50052 Certaldo (Firenze) Italia