



Semiautomatic, multispindle, singlehead boring machine

BORING SYSTEM 35

For horizontal and vertical drilling into woodbased panels and solid wood, for the furniture manufacturing






FAST HORIZONTAL DRILLING

Thanks to the 1.088 mm interaxis and the large working table, You can process 2 panels having 540 mm width at the same time



FAST VERTICAL DRILLING

You can process 3000 mm - long sides in 3 working cycles



PERFECT PANEL JOINTS

The ref. side fences, adjustable on numeric counters, always represent a precise reference point, quick to setup, and guarantee perfect parallelism of the drilling operations.

Equipped with n.2, 2HP, motors, unique of its kind, for a powerful and well-balanced drilling

Max. drilling depth up to 85 mm

Small footprint: 1,5 sqm

It's two times faster than a manual boring machine



BORING SYSTEM 35

SERVICE

Worldwide after-sale service.

Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs

DATA SHEET

Spindles	N 35
Left and right spindles	N. 17 left - N. 18 right
Spindle interaxis	32 mm
Total interaxis:	1088 mm
Max. tool diameter	40 mm
Max. boring depth	85 mm
Max. boring height	55 mm
Height of the working table	860 mm
Max. panel thickness	60 mm (130 mm optional)
Max. panel dimensions	1335 x 3000
N° 2 motors	HP 2 / KW 1,5 - RPM 2800
Standard pneumatic pressure	BAR 6/8
Air consumption	10 NL / cycle
Dust collection hood diameter	80 mm
Overall dimensions - net weight:	1670 x 990 x 1280 - kg 367
Package dimensions (machine)	1450x 950 x 1070
Package dimensions (long fences)	1500 x 120 x 60
Gross weight	kg 406









QUICK SET-UP

Adjusting the boring depth is extremely easy with the "Spyral System" device and the 10 mm automatic reset for vertical drilling

VERSATILITY

It drills at any angle between 0° and 90°

SAFE PANEL HOLD-

The quick-positioning, safety, holddown clamping units ensure the greatest stability and steadiness of the working piece during the working cycle and the highest accuracy of the drilling process

SERVICE

+39 0571 635 433 service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com





Via delle Regioni, 299 50052 Certaldo (Firenze) Italia