




Professional power-feeding unit with fixed speeds


STEFF 2048

Safety device for a safe and effective workpiece feeding on different types of traditional wood-working machines



HIGH-QUALITY END PRODUCTS

4-wheel model: the ideal solution for the feeding of wooden rods and medium and/ or large-size workpieces. Thanks to the two infeed-wheels and the two outfeed ones, the workpiece is constantly and evenly feeded althrough the working process, thus remarkably improving the quality of the end products.



QUICK SET-UP WITH GEAR SHIFT

The speed selector allows a quick setup of the 1st and the 2nd feeding rate and the quick change of the feeding direction back and forth. First 4 speeds are obtained by swapping the internal gears, while turning the gear lever You can get the additional 4 speeds easily and fast.



PERFECT GRIP

50-Shore wheels made of patented "Feeder Grip" rubber, provide the longest durability and the highest grip on the workingpiece. 4 wheels ensure even more grip on the panels, althrough the feeding process.

Improves the safety: the operator does not have to put his hands close to the tool
Improves the finish quality, thanks to the constant and even feed-rate
Feed-rate can be easily selected to meet every specific working need
Easily adjustable to suit different sizes of work piece



SERVICE

Worldwide after-sale service.

Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs


DATA SHEET

| N. of speeds back and forth | 8 |
|---|---|
| Fixed speeds | 2 - 4 - 5.5 -6.5 - 11 - 13 - 16.5 - 33 mt/min |
| N. of wheels | 4 |
| Wheel diameter and thickness | 120 x 60 mm |
| Motor | 1 HP / 0,75 KW RPM 1400 /2800 |
| Wheel suspention | 20 mm |
| Distance between wheels | 0000 133 mm - 143 mm - 145 mm |
| Distance between first and last wheel | Q Q Q Q 421 mm |
| Overall dimensions and net weight of the feeding unit | 615 x 220 - 490 mm 35Kg |
| Overall dimensions and net weight of the stand | 540 x 910 mm 35 Kg |
| Package dimensions and gross weight (feeding unit) | 670 x 570 x 330 mm 37 Kg |
| Package dimensions and gross weight (stand) | 800 x 330 x 330 mm 37 Kg |



SAFETY AS A CORE VALUE

A power-feeder improves the safety as it feeds the workpiece close to the tool, while operator's hands are kept at a distance. Its effectiveness depends on specific design and manufacturing criteria. Maggi feeders are the only ones designed and manufactured in Italy and abiding by all EU safety norms.



UNIVERSAL STAND

For easy positioning and adjusting of the feeding unit on the machine tool. It is easy to fix, stable and strong: foot, cross-shaped piece, pipe, joint and collar are made of cast-iron and the two columns are made of rectified steel of considerable thickness.

SERVICE +39 0571 635 433 service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com



MAGGI TECHNOLOGY

Via delle Regioni, 299 50052 Certaldo (Firenze) Italia





Stand for professional power-feeding units

PATENTED

"EASY" STAND

Makes it FAST and EASY to tilt your power-feeding unit







UNIVERSAL PATENT

The innovative, patented EASY swivel joint is compatible with all Maggi stands, even older ones, while its compatibility with other brands is to be confirmed after checking

READY IN ONE CLICK

Tilting Your power-feeding unit has never been so QUICK and EASY! Turn the handle to unlock , tilt the feeding unit, turn the handle again to lock

UNCOMPROMISED SAFETY

The safety knob prevent the feeding unit from falling or moving suddenly after unlocking the handle; thus allowing the operator to tilt and adjust it in complete safety.

- VALUE EVERY MOMENT: Both in Your business and in Your life every minute counts! With EASY STAND You can move faster and get to the job done easier.
 - UPGRADE SMARTLY: Replacing Your traditional swivel joint with an EASY joint considerably improves the performance of your stand at very little cost.





SERVICE

+39 0571 635 433 service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com

MAGGI TECHNOLOGY

Via delle Regioni, 299 50052 Certaldo (Firenze) Italia

