



Professional power-feeding unit with variable speeds

## STEFF SUPERSONIC 3

Safety device for a safe and effective workpiece feeding on different types of traditional wood-working machines



## HIGH-QUALITY END PRODUCTS

3-wheel model : the ideal solution for the feeding of laths and medium or small-size workpieces. Thanks to the two infeed-wheels and the third outfeed one, the workpiece is constantly and evenly feeded althrough the working process, thus remarkably improving the quality of the end products.



# TOP OF THE RANGE, ELECTRONIC

A wide range of variable speeds ( 0,5 to 33 m/min) with electronic selection and read-out display. The ideal solution for those, who often need to change the feeding rate. By pushing a botton on the motor You can easily change the feeding direction back and forth



### **PERFECT GRIP**

50-Shore wheels made of patented "Feeder Grip" rubber, providing the longest durability and the highest grip on the workingpiece

Improves the safety: the operator does not have to put his hands close to the tool
Improves the finish quality, thanks to the constant and even feed-rate
Feed-rate can be easily selected to meet every specific working need
Easily adjustable to suit different sizes of work piece



### **STEFF SUPERSONIC 3**

## **SERVICE**

Worldwide after-sale service.

Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs


### **DATA SHEET**

Variable speeds	from 0,5 to 25 mt/min (up to 33 m/min optional)
N. of wheels	3
Wheel diameter and thickness	120 x 60 mm
Motor	1 HP / 0,7 KW RPM 1400 /2800
Wheel suspention	20 mm
Distance between wheels	000 133mm - 153 mm
Distance between first and last wheel	○ ○ ○ 286 mm
Overall dimensions and net weight of the feeding unit	474 x 220 x 490 mm 36 Kg
Overall dimensions and net weight of the stand	540 x 910 mm 35 Kg
Package dimensions and gross weight (feeding unit)	670 x 570 x 330 mm 38 Kg
Package dimensions and gross weight ( stand)	800 x 330 x 330 mm 37 Kg



# SAFETY AS A CORE VALUE

A power-feeder improves the safety as it feeds the workpiece close to the tool, while operator's hands are kept at a distance. Its effectiveness depends on specific design and manufacturing criteria. Maggi feeders are the only ones designed and manufactured in Italy and abiding by all EU safety norms.



### **UNIVERSAL STAND**

For easy positioning and adjusting of the feeding unit on the machine tool. It is easy to fix, stable and strong: foot, cross-shaped piece, pipe, joint and collar are made of cast-iron and the two columns are made of rectified steel of considerable thickness.

**SERVICE** +39 0571 635 433 service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com



### MAGGI TECHNOLOGY

Via delle Regioni, 299 50052 Certaldo (Firenze) Italia